

170 Lm/W



PROE

LED Flood Light

LSHM-200W-LV(XXK)ProE

200W

For area lighting for applications:

Tunnel Lighting | Road tunnel | Stadiums |
Shopping Centers | Prisons | Expressways |
Industrial Facilities and Railway Terminals etc.






SILM PROE SERIES

SILM PROE Series LED Flood LIGHT is built with robust Folding aluminum fin module housing and heavy duty anticorrosive surface treatment for sparking the beauty and improving lighting conditions of applied area. Originated by the demand for Area lighting applications SILM PROE Series flood lights can be extended to 240W and fixture efficacy reaches to 170lm/w, better brilliance less energy consumption.

IP66 WATERPROOF & IK10

- 1.High luminaire efficiency up to 170lm/w
- 2.Marine grade aluminum housing
- 3.IP66 and IK10 protection rate
- 4.5 years warranty
- 5.Folding aluminum fin design which are very light weight



Folding Aluminum Fin Design

Folding aluminum fin design which are very light weight. Increase the heat dissipation surface area by air cooling to dissipate heat and expand the contact area with air! It speeds up the spread of heat! Thermal effect is good! Compared with traditional die-cast aluminum and profile aluminum, which is heavier and there are certain safety risks. On the contrary ,the aluminum fin heat sink are more secure.



SLIM PROE SERIES

LED Flood Light




▼ Features

1. High luminaire efficiency up to 170lm/w
2. Marine grade aluminum housing
3. IP66 and IK10 protection rate
4. 5 years warranty
5. Folding aluminum fin design which are very light weight
6. ETL DLC TUV CE CB SAA RoHS LM79 LM80 TM21 IK10 Salt Spray test approved

5
Years
Warranty

50000 Hour
Long Service Life

▼ Dimension



SLIM PRO

LED Flood Light



- Light Source: Luminleds 3030
- Input Volt: 100-277VAC
- IP Rating IK Rating : IP66 & IK10
- Beam Angle: 15° 25° 40° 60° 90° 120° 30x70° 49x21° 136x78°
- Color Temp: 3000K 4000K 5000K 5700K 6000K
- Size: 306.6x406.5x104mm
- Weight: 4.2Kg
- 5 years warranty



100-277V

347-480V

Dimmable

50,000H

Adjust

-30~45°C

IK10


IP66

Folding Aluminum Fin


Technical Specifications

Model	LSHM-200W-LV(XXK)ProE	LSHM-200W-LV(XXK)ProE
Watt	200W	200W
Efficiency	140LM/W±3%	170LM/W±3%
Size	306.6x406.5x104mm	306.6x406.5x104mm
Lumen	28000Lm	34000Lm
Driver	Meanwell Driver XLG-240-H-A	Meanwell Driver XLG-240-H-A


Beam Angle




15°




25°




40°




60°




90°




120°



30x70°




49x21°



136x78°

Application



Tunnel Lighting



Flood Lighting



Basketball lighting



Parking Lot Lighting


For area lighting for interior and exterior applications:

Tunnel Lighting, Flood lighting, factories, plants, warehouse, exhibition halls, gym, high mast lighting and etc.

Installation



Wall Installation



Ground Installation



Pole Installation

Package details

Wattage	Size of Box	Weight	Box Quantity
200W	37x47x15cm	4.6Kg	1PC